



## MATERIALS:

**Valve** — Chrome-plated brass cylinder. Stainless steel spring. U-packing seal and duckbill. Corrosion-resistant to most soaps and detergents. Equipped with nut, washer, supply tube, and PVC mounting 3-Barb adapter.

**Container** — Translucent, shatter-resistant polyethylene. Capacity: 1.0-L (34-fl oz).

## OPERATION:

Push-in valve dispenses vegetable-oil liquid soaps, viscous lotion soaps, and synthetic detergents. Valve is operable with one hand, without tight grasping, pinching, or twisting of the wrist. Spring Replacement Kit available, order Part No. 8601-29.

## INSTALLATION:

Valve is designed for installation through 18mm (23/32") diameter hole in 32 to 50mm (1-1/4" to 2") thick panel. Thread sealing tape, such as Teflon tape or similar, is recommended as a sealant on the exposed threads of the adapter where the soap valve threads onto it.

## SPECIFICATIONS:

Soap valve shall dispense vegetable-oil liquid soaps, viscous lotion soaps, and synthetic detergents. Valve shall be equipped with chrome-plated brass cylinder, stainless steel spring, U-packing seal, and duckbill. Adapter shall accommodate mounting thicknesses up to 50mm (2"). Translucent, shatter-resistant polyethylene container shall have a capacity of 1.0-L (34-fl oz).

**Panel-Mounted Soap dispenser shall be Model B-8601 of Bobrick Washroom Equipment, Inc., Clifton Park, New York; Bobrick Washroom Equipment Bobrick; Jackson, Tennessee; Los Angeles, California; Bobrick Washroom Equipment Pty. Ltd., Australia; and Bobrick Washroom Equipment Limited, United Kingdom.**