

Opal CleanflushTM Easy Height

Sanitary Compartment - Ambulant Applications

4.5/3 litre Vitreous China Wall Faced Close Coupled Toilet Suite



The polished and streamlined design of the **Opal** range brings style and functionality to the bathroom environment. The added hygiene of the Cleanflush[®] rimless flushing system makes the range ideal for hospital, aged care and commercial applications where the absolute highest levels of hygiene and rapid cleaning are required. The inclusion of a raised height pan, extra projection and optional armrests make it an ideal solution for aged care applications.

Important: Reference must be made to AS 1428.1-2021 with current amendments to determine circulation space, grab rail and installation requirements. The dimensions in this sheet may change with amendments to the standard.

Pan: Opal Cleanflush[®] Easy Height 4.5 litre full flush washdown rimless pan with a fully glazed trap.

Traps: Universal trap for S or P-trap installations.

Cisterns: Opal Cleanflush[®] cistern – has a free fitting lid and is suitable for domestic and light commercial applications. Available as internal overflow. Standard back entry only.

Vandal Resistant Conversion Kit – A simple to install conversion kit is available for the standard mechanism to lock the lid onto the cistern, recommended for use in heavy duty commercial areas. Code No.750109.

Cistern inlet stop valve and inlet flex tube connection is concealed within the cistern and is included. **Important: Working pressure minimum 30kPa to maximum 1000kPa flow pressure. Rain water tank compliant. Accurate wall setout for B.S.P. 1/2" Nipple water inlet connection is essential.**

Buttons: Round Button - Chrome (supplied). Other button options sold separately. See section 4 - CARE BUTTONS for further details.

Fixing: The cistern is fixed directly to the pan with a robust concealed base fixing system without the need for wall fixing.

Seats: Includes **Opal II** normal close single flap or soft close double flap seat in Caroma White (W) or normal close double flap seat in Black (B) and Anthracite Grey (AG). See Section 3 - SEATS for further details.

Colour: White only.

Installation: The installation of the toilet suite shall be in accordance with the normal minimum drainline grade requirements in AS/NZS 3500.2.

Dimensions: All dimensions are in millimetres and are subject to normal manufacturing variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications without notice.

