



Circa Wall basin mixer system Dress kit

SUSSEX



Product code

RWBMS150RH	Wall basin mixer system 150mm	RWBMS150RH-V	Wall basin mixer system 150mm - Vertex
RWBMS200RH	Wall basin mixer system 200mm	RWBMS200RH-V	Wall basin mixer system 200mm - Vertex
RWBMS250RH	Wall basin mixer system 250mm	RWBMS250RH-V	Wall basin mixer system 250mm - Vertex

Mixer dress kit


- Remove Mixer protective cover.
- Using silicone, seal the wall surface around the Mixer and Outlet threads.
- Fit the Mixer Dress Ring.
- Fit the Handle Body onto the Mixer Cartridge Lever and ensure full engagement.
- Secure the Handle Body by tightening the Set screw using the Allen Key provided (tighten well).

Outlet fit off

- Apply sealing tape (Teflon) to male thread.
- Place Dress Ring over outlet.
- Push Dress Ring back to meet the wall.
- Fit and align the Outlet.
- To complete installation, operate the Mixer(s) checking the flow of both hot and cold water from the Outlet. Check all fittings and fixtures for water leaks.

Circa Wall basin mixer system Rough in

SUSSEX



Product code

RWBMS150RH	Wall basin mixer system 150mm	RWBMS150RH-V	Wall basin mixer system 150mm - Vertex
RWBMS200RH	Wall basin mixer system 200mm	RWBMS200RH-V	Wall basin mixer system 200mm - Vertex
RWBMS250RH	Wall basin mixer system 250mm	RWBMS250RH-V	Wall basin mixer system 250mm - Vertex

Rough in plumbing

- Prior to installing calculate the finished wall thickness, maximum is 30mm thick. Contact manufacturer for further options.
- If Wall thickness is greater than 30mm, contact manufacturer for further options.
- Prepare a Nogging to be fixed parallel between the Wall Studs.
- The Nogging must be fitted to enable the base of the Masterfit to be 30-32mm back from the Stud Face.
- The Masterfit will be marked "This side Up" to indicate orientation.
- Using the screws (x4) provided, mount the Masterfit to the Nogging. Ensure the Master fit is level and square.

Pipe connections

- The Hot and Cold ports are marked on the Masterfit. (Mixers have individual Hot/Cold inlet ports).
- Flush all water feed lines. All lines must be free from any dirt and debris before connecting to the Masterfit.
- Connect Hot and Cold lines to the corresponding 1/2" BSP ports of the Masterfit. (see Drawing)
- Do not remove any factory fitted pressure plugs or Fixings.
- Once all water connections are made, check Hot/Cold water flow by operating the Mixer Cartridge.
- Check all fittings and fixtures for leaks.
- Leave the Mixer(s) in the closed position and replace the Mixer protective cover.
- Store the Dress Kit in a safe place until required (see Dress Finishing Guide).

Plumbers note

- On-site high pressure line testing must be conducted with the Mixer in the closed position. (STATIC TEST ONLY)
- Under no circumstances is the Mixer to be opened when exceeding the maximum stated water pressure.
- At the completion of the testing, do not relieve any high pressure by opening the Mixer.
- Exposing the internals of the Mixer Cartridge to higher than specified water pressures, will void the manufacturer's warranty.



AS/NZS 3718:2005
LIC. 20081