



EAN: 4057304014338
static.hansa.com/090228333



- Washbasin
- Single-lever
- Deck mounted
- Matt black
- Fixed spout
- PCA® - constant flow rate regardless of pressure variations
- Hot/Cold symbols, Single operating lever/handle
- Limitation option for maximum temperature and flow-rate, Adjustable hot water stop (included, retrofittable)
- ø 35 mm ceramic cartridge for flow and temperature control
- Flexible inlet pipes
- Inner body made of DZR brass, Rapid installation system
- Without pop-up waste, Without draw-rod opening



Technical data

Flow properties

Flow-rate at 3 bar (with flow controller)	6.0 l/min
Pressure loss with flow (0.1 l/s)	2 bar

Technical properties


DN-size (nominal dimension)	DN15
Hot water supply	max. +70°C
Working pressure	1-10 bar
Connection size	G3/8
Projection	123 mm
Backflow prevention (EN1717)	AA
Material	Brass

Regulations


EN standard	EN 817
Noise class	I (ISO 3822)

Approvals and Declarations

KIWA	K6116/08
DVGW	NW-6506CQ0410
ABP	P-IX 38553/IA
Declaration of conformity	DoC



Spare parts



SP0902228333

	Name	Code
01	Temperature adjustment limiter	59912325
02	Tightening nut, M40x1	1003409V
03	Cartridge, 3.5 Classic	59913075
04	Fixing screw, M8x1, L=140	59912474
05	Bottom seal	59914591
06	Fixing set	59910749